

LASER AND THERMAL CAMERAS

AUTOLIVELLO BRAVO LASER ROTATIVO H4



DETAILS

- Automatic laser level with visible rotating red beam: generates a horizontal self-leveled plane and the plumb line
- Dust/Waterproofing IP 66 resists completely to dust.
Water protection: protected against water splashing from any direction
- SCANNER function to draw a more visible and shorter line with 4 different lengths
- SLOPE Function
- MANUAL function that excludes automatic leveling and allows to tilt the device for tracing inclined planes
- TILT function: in case of accidentally moving the unit, the beam stops
- 4 rubber handles for easy and effective grip
- Remote control receiving on 4 sides of the unit

TECHNICAL DATA SHEET

| PARAMETER | VALUE |
|----------------------------|--|
| Leveling accuracy H. | ± 3 mm / 30 m |
| Self-leveling range | ± 5° |
| Autonomy | 30 hour |
| Working range | diam 500 m (depending on weather conditions) |
| Rotational speeds | 0-60-120-300-600 rpm |
| Scanner function | 0° - 10° - 45° - 90° - 180° |
| Tilt function | si |
| Laser type | 635 nm, 1mW |
| Laser output | Class 2 |
| Power supply | 4 x NiMH C4000mAh 1,2 V rechargeables |
| Dimensions | 220 x 220 x 210 mm |
| Operating temperature | -10 °C / +50 °C |
| Weight (without batteries) | 3,5 kg |
| Impermeability | IP 66 |

| PARAMETER | VALUE |
|------------------------------|--------------------|
| Tripod thread | 5/8" |
| Remote control distance | 30 / 10 m (in/out) |
| Batteries for remote control | 2 x 15 V DC |
| Battery for the receiver | 1 x 9 V DC |

ARTICLES OF THE RANGE

| Ref. |  |  |
|-------|---|--|
| 61385 | 8001066613854  | 1 |

GALLERY

