

LASER AND THERMAL CAMERAS

BRAVO LASER ROTATIVO HV4 GREEN



DETAILS

- Automatic laser level with visible rotating green beam: generates a horizontal self-leveled plane and the plumb line
- High-sensitivity 4-line receiver
- Metal cover
- IP 66 dust/waterproofing: protected against ingress of dust and water
- By rotating the unit 90°, the unit generates a vertical self-leveled laser plane and two horizontal beams.
- SCANNER function to project a more visible and shorter line (adjustable to 4 lengths)
- SLOPE function (manual inclinations X, Y)
- MANUAL function, which excludes automatic levelling and allows the unit to be tilted at will
- TILT function: In case of unintentional movement the device switches off the laser beam.
- Laser with 4 rubberized handles for easier grip and increased protection
- Receiving the remote control on the 4 sides of the unit
- LED battery charge indicator
- Li-ion rechargeable battery.

TECHNICAL DATA SHEET








PARAMETER	VALUE
Leveling accuracy	horizontal ± 3 mm / 30 m
	vertical ± 5 mm / 30m
Self-leveling rang	$\pm 5^\circ$
Autonomy	~ 35 hours
Working range	500 m (with receiver)
	on climatic conditions
Rotational speeds	0-60-120-300-600 rpm
Scanner function	10° - 45° - 90° - 180°
Tilt Function	yes
Out of levelling signal	yes
Laser type	515/638 nm, <1 mW
Laser output	Class 2

PARAMETER	VALUE
Power supply	4 x Li-ion 4000mAh 1,2 V
Dimensions	220 x 220 x 210 mm
Operating temperature	-10 °C / +50 °C
Weight (without batteries)	3,5 Kg
IP Protection	IP 66
Tripod thread	5/8"
Remote control distance	30 / 10 m (in/out)
Batteries for remote control	2 x 1,5 V DC
Batteries for the receiver	1 x 9 V DC

ARTICLES OF THE RANGE

Ref.		
61395	8001066613953	1

GALLERY

	 REMOTE CONTROL	 LI-ION BATTERY	 BATTERY CHARGE INDICATOR	
	 10°/45°/90°/180°	