

LASER AND THERMAL CAMERAS

# GROUND 360



## DETAILS

- Green laser level. Projects: a horizontal plane over 360° plus a vertical plane at 90° to form 1 wall cross.
- Easy ceiling positioning (
- Laser with adjustable intensity
- Indoor/outdoor use (with receiver not included Code 60749)
- Automatic flashing of the laser if the device is out of the self-leveling range
- Automatic locking system to avoid vibrations during transport
- Compact design, non-slip and shockproof rubber coating
- ¼" connection for the tripod
- Magnetic base and metal cap for easy stacking
- Ion-Li batteries rechargeable via USB cable supplied

## TECHNICAL DATA SHEET

PARAMETER	VALUE
Capacity (depending on ambient brightness)	30 m (Ø 60 m)
Capacity with receiver	50 m (Ø 100 m)
Leveling accuracy	± 3 mm / 10 m
Self-leveling range	± 4°
Signal out self-leveling	yes
Laser type	505-550 nm < 1mw
Laser power	Classe II
Rechargeable batteries	3,7 4400 mAh li-ion
Dimensions (mm)	104 x 83 x 83
Weight	0,450 Kg
Dust/Waterproofing	IP 54
Tripod thread	1/4"

# ARTICLES OF THE RANGE

Ref.



61425 80010666143257 1

## GALLERY

