

LASER AND THERMAL CAMERAS

DOUBLE 60+60 ALU



DETAILS

- Exclusive HSA (Horizontal Sound Assistant) function
- 120 m range (internal): 60 m (front) + 60 m (rear)
- Possibility of selecting front or rear beam only
- Aluminium body
- Black and white screen selection
- Rear built-in magnet
- Horizontal/vertical inclinometer and 0° and 90° indicator
- Screen rotation
- Room Painter function
- Accuracy ± 2 mm unidirectional
- 5 Pythagorean functions
- Built-in rechargeable battery, USB-C

TECHNICAL DATA SHEET

PARAMETER	VALUE
Working range	60m (unidirectional internal) 120m (bidirectional internal)
Accuracy	$\pm (2\text{mm}+d * 1/10000)$ *
HSA Technology	yes
Angular measuring range	$\pm 90^\circ$
Continuous measurement	yes
Surface/volume measurement	yes
Pythagoras	yes
Minimum/maximum	yes
Addition/subtraction	yes
Auto-calibration	yes
Electronic level bubble	yes
Automatic screen rotation	yes
Black/White screen switching	yes

PARAMETER	VALUE
Magnetic Base	yes
Laser class	II
Laser type	630-670nm, <1mW
Automatic diode switch-off	20s
Device switches off after	180s
Battery life	8000 measurements
Beep	yes
Storage temperature	-20°C~60°C
Operating temperature	0°C~40°C
Maximum humidity	20%~80% RH
Batteries	Ion-Li 3,7V 850mAh
Dimensions	115x50x24.5mm

ARTICLES OF THE RANGE

Ref.	L	Barcode	Image
61662	0,05 - 120 m	8001066616626	1

GALLERY

