

LASER AND THERMAL CAMERAS

EARTHMOVING CONTROL-RECEIVER



DETAILS

- Can be used for both red and green lasers
- It allows the control of the leveling of the ground on earthmoving machines
- Intercepts the signal from any rotary laser
- Length of the receiving bar 25 cm on a 360° arc
- Luminescent diodes intercept the laser line
- Equipped with screwed brackets to fasten the device on earthmoving machines
- Double choice of accuracy
- IP 66 dustproof and waterproof protection
- Remote control device in the cabin
- Supplied with 220 V battery charger, 12 V cable to the vehicle battery, connecting cable between the receiver and remote receiver
- Battery duration 40 hours
- Ref. 60871 - 2 clamp locks (spare)
- Ref. 60872 - 2 magnet locks (spare)

TECHNICAL DATA SHEET

PARAMETER	VALUE
Fine accuracy	± 2 mm / ± 10 mm
Rough accuracy	± 5 mm / ± 23 mm
Batteries	7,2 V NiMh/2500 mAh, Charger
Autonomy	± 40 hours
Recharge time	± 15 hours
Size	376 x 180 x 60 mm
Operating temperature	-20 °C / +50 °C
Weight (without batteries)	3,10 Kg
Impermeability	IP 66

ARTICLES OF THE RANGE

Ref.		
60895	8001066608959	1

GALLERY

